



## \*\* DESCRIPTIONS NOT GUARANTEED! USE AS A GUIDE ONLY PLEASE DO YOUR OWN ONSITE INSPECTION \*\*

30 TON WABASH HYDRAULIC MOLDING PRESS 4 post upstroke type; floor standing

Distance between 1.75" dia. posts: 16.5" L-R x 7" F-B Platen area (nominal): 15" L-R x 12" F-B Stroke of fully guided platen: 0 - 7" maximum

Daylight opening (total):

Daylight opening between

mounting plates (1): 10"-20" maximum (adjustable) Mounting plates (2): 15" L-R x 12" F-B x 1" thick Main ram diameter (1): 3.75"/2" @ 5430 PSI - 30 tons

Floor to top of moving platen: 42"

Power unit (base of press): (2) Hydraulic pumps, driven by 1 HP 1800 RPM 220/3/60 motor

Speeds approx.: 35"/minute closing

3"/minute pressing to 30 tons

12-22" maximum (adjustable)

50"/minute return

Controls: Pushbutton operation with stroke &

pressure control
Dual palm buttons
Cycle timer

Cycle timer Pressure gauge

Weight approx. 1,800 lbs.

Overall dimensions approx. 36" L-R x 42" F-B x 72" H  $\,$ 

Serial no. N/A