



2100 Stonington Avenue, Hoffman Estates, IL 60169

(847) 380-9819

www.heathindustrial.com * auctions@heathindustrial.com

**** DESCRIPTIONS NOT GUARANTEED! USE AS A GUIDE ONLY PLEASE DO YOUR OWN ONSITE INSPECTION ****

30 TON PHI SQ-244C-AM4 MOLDING & LAMINATING PRESS

Hydraulic

Slab side upstroke type; floor standing

Distance between slab sides: 20" L-R

Platen area (nominal): 19" L-R x 12" F-B

Stroke of guided platen: Approx. 0 - 4" maximum

Daylight opening (total): 13" maximum

Daylight opening between
hot plates (1): 8" maximum

Hot plates (2): 18" L-R x 12" F-B
(electrically heated to 600° F -
water cooled)

Insulation (2): 18" L-R x 12" F-B

Main ram diameter (1): Approx. 5" @ 3055 PSI - 30 tons

Floor to top of moving platen: 37"

Power unit (base of press): Hydraulic pump, driven by
1 HP 1200 RPM 220/440/3/60 motor
Controls: Pushbutton operation with stroke &
pressure control

Dual palm buttons

Selector switch for manual/auto

(3) cycle timers

Temperature controller

Pressure gauge

Weight approx. 1500 lbs.

Overall dimensions approx. 48" L-R x 24" F-B x 60" H

Serial no. 5526