

** DESCRIPTIONS NOT GUARANTEED! USE AS A GUIDE ONLY PLEASE DO YOUR OWN ONSITE INSPECTION **

12 FT. X 12 GA. NIAGARA HYDRAULIC PRESS BRAKE Model no. HBM-100-10 Bending capacity: 12' x 12 ga. mild steel 10' x 10 ga. mild steel $8' \times 3/16"$ mild steel Tonnage capacity: 100 tons Overall length of bed & ram: 12' Stroke: Open height: 14" 7" Closed height: 7" Throat depth: Width of bed: 3" Floor to top of bed: 36" Speeds approx.: 166"/minute rapid advance 20"/minute anti-backbend 166"/minute rapid return EQUIPPED WITH: 24" Autogauge CNC 1000 single axis back gauge with vertical adjustment Free standing control with dual palm buttons & emergency stop button Electric foot switch Pushbuttons for ram up - down - inch Key selector switches for hand - foot; auto return - manual return; rapid to anti-backbend - anti-backbend; inch - off - single stroke Power tonnage control Ram tilt adjustment Front operated micrometer type fine tilt adjustment Sectional ram die clamps (4) T-slots in top of bed Dovetail slot in front & back of bed Hydraulic pump, driven by 7.5 HP 1750 RPM 230/460/3/60 motor Weight approx. 15,000 lbs. Overall dimensions approx. 153" L-R x 60" F-B x 102" H $\,$ Serial no. P54440