



** DESCRIPTIONS NOT GUARANTEED! USE AS A GUIDE ONLY PLEASE DO YOUR OWN ONSITE INSPECTION **

60 TON STAMTEC G1-60-S O.B.I. PUNCH PRESS

Model G1-60-S

Air clutch; air counterbalances, back geared type

Stroke: 5"
Slide adjustment: 3"

Shut height S.D.A.U.: 13.3" to top of bed Area of bed: 35" L-R x 20" F-B Bolster thickness: 3-3/4" (T-slotted)

Bolster thickness: 3-3/4" (T-slotted)
Area of slide: 19-1/2" L-R x 14-1/4" F-B (T-slotted)
Shank hole diameter: 2-1/2"

Shank hole diameter: 2-1/2"
Throat depth: 10.6"
Opening through back: 21.1"
Floor to top of bed: 28"
S.P.M. approx.: 60

EQUIPPED WITH: Dual palm buttons for run Pushbuttons for start - stop,

motor forward - reverse

Key selector switch for inch - off -

single - continuous

Pushbuttons for motor forward - reverse - off

Crank position indicator Automatic oil lubrication

Front to back crankshaft design

Knockout slot in slide 5 HP 440/3/60 motor

Weight approx. 10,600 lbs.

Overall dimensions approx. 45" L-R x 72" F-B x 110" H

Serial no. 01-60S-0001