



** DESCRIPTIONS NOT GUARANTEED! USE AS A GUIDE ONLY PLEASE DO YOUR OWN ONSITE INSPECTION **

75 TON BLISS #C-75 O.B.I. PUNCH PRESS Model no. C-75 Air clutch & brake; air counterbalances; flywheel type 4" Stroke: Slide adjustment: 3-1/2" Shut height S.D.A.U.: 17" to top of bed 36" L-R x 24" F-B 3-1/2" (T-slotted) 24" L-R x 18" F-B (T-slotted) Area of bed: Bolster thickness: Area of slide: Shank hole diameter: 2-5/8" Throat depth: 13" Opening through back: 19"
Floor to top of bed: 36" S.P.M. approx.: 60-120 EQUIPPED WITH: Free standing control with dual palm buttons for run with emergency & top stop buttons Push-pull button for start - stop Key selector switches for inch - off - single - cont.; slide adjustment off - on; motor forward - reverse Variable speed adjustment with control for slow - fast Trabon automatic oil lubrication Rotary cam limit switches Knockout slot in slide Air surge tanks 10 HP 1730 RPM 230/460/3/60 Reliance variable speed

Weight approx. 21,000 lbs.

Overall dimensions approx. 80" L-R x 95" F-B x 137" $\rm H$

drive motor

Serial no. H69976